

DS-2CE71H0T-PIRLO 5 MP PIR Fixed Turret Camera



- 5 MP PIR turret camera
- PIR detection, strobe light alarm and alarm out to warn off intruders in real time
- EXIR 2.0: advanced infrared technology with 20 m IR distance
- Water and dust resistant (IP67)

▪ Specification






| Camera | |
|-------------------------|--|
| Image Sensor | 5 MP CMOS image sensor |
| Max. Resolution | 2560 (H) × 1944 (V) |
| Min. Illumination | 0.01 Lux @ (F2.0, AGC ON), 0 Lux with IR |
| Shutter Time | PAL: 1/20 s to 1/50,000 s NTSC: 1/20 s to 1/50,000 s |
| Day & Night | ICR |
| Angle Adjustment | Pan: 0° to 360°, Tilt: 0° to 75°, Rotate: 0° to 360° |
| Signal System | PAL/NTSC |
| Light Alarm | Yes |
| Lens | |
| Lens Type | 2.8 mm, 3.6 mm fixed lens |
| Focal Length & FOV | 2.8 mm, horizontal FOV: 85.5°, vertical FOV: 63.8°, diagonal FOV: 110.7° 3.6 mm, horizontal FOV: 80.1°, vertical FOV: 63.8°, diagonal FOV: 105.9° |
| Lens Mount | M12 |
| Image | |
| Image Parameters Switch | STD/HIGH-SAT |
| Image Settings | Brightness, Sharpness, DNR, Mirror, Smart IR |
| Frame Rate | TVI: 5 MP@20fps, 4 MP@25fps, 4 MP@30fps, 1080P@25fps, 1080P@30fps |
| Day/Night Mode | Auto/Color/BW (Black and White) |
| White Balance | Auto/Manual |
| White Light | AUTO/OFF |
| AGC | Support |
| Interface | |
| Video Output | 1 HD analog output |
| General | |
| Material | Enclosure: Plastic Main body: Metal |
| Dimension | Φ 109.8 mm × 89.75 mm (Φ 4.32" × 3.53") |
| Weight | Approx. 327 g (0.72 lb.) |
| Operating Condition | -40 °C to 60 °C (-40 °F to 140 °F), humidity: 90% or less (non-condensation) |
| Communication | HIKVISION-C |
| Language | English |
| Power Supply | 12 VDC ± 25% |
| Consumption | Max. 3.5 W |
| IR Range | Up to 20 m |
| Approval | |
| Protection | IP67 |

▪ Available Model

DS-2CE71H0T-PIRLO

▪ **Accessory**

▪ **Optional**

| DS-1272ZJ-110-TRS Wall Mount | DS-1275ZJ-SUS Vertical Pole Mount | DS-1276ZJ-SUS Corner Mount | DS-1280ZJ-S Junction Box | DS-1281ZJ-S Inclined Ceiling Mount |
|---|---|---|---|---|
|  |  |  |  |  |
| DS-1280ZJ-TR13 | | | | |
|  | | | | |

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.

